

# **Datasheet**

# PBO - Architectural handles, 400kg or 800kg

### **Product Description**

Pull handles are becoming increasingly popular with sites that require strong holding force or more aesthetic solutions. The entire range from CDVI is ideal for locations where a stronger lock is essential, such as schools, halls of residence, and other public buildings.

The PBO is available in 400mm with 1x400kg maglock or 600mm with 2x400kg maglocks. They can both be fitted to new or existing doors and are suitable for external installation.

PBO handles offer higher holding force, increasing the security and strength of the locking solution.





## **Key Features**

- Surface mount architectural
- Retrofit or new build
- Aesthetic profile
- Quick and easy installation
- Up to 400kg or 800kg holding force
- Suitable for wooden, metal, & glass doors





DEEE


**RoHS** Certification



100kg side load (NFS)



-25°C to 70°C





### **Product Specifications**

Material: Satin anodised aluminium

Mounting: Surface Lock mode: Fail safe

**Holding force:** 

1 maglock: 400kg2 maglocks: 800kg

**Relays:** 1 (2 for 2 maglock version)

**Contacts:** COM/NO/NC

Weight:


1 maglock: 3.15kg2 maglocks: 5.35kg



Power input: 12/24Vdc

Consumption: 550mA @ 12Vdc

275mA @ 24Vdc



## **Range References**

F0519140000 PBO400RN40 Architectural handle, 1x400kg monitored magnet, 400mm F0519000056 PBO800RN60 Architectural handle, 2x400kg monitored magnets, 600mm

