



STAINLESS PIEZO BUTTON

EXIT BUTTONS

Market leading exit buttons, that is both hard wearing and cost effective. Suitable for use in applications up to 30V.



IEPS/PTE



SPECIFICATION	FEATURES	OTHER PRODUCTS
---------------	----------	----------------

IEPS/PTE

- Contacts: NO/COM
- Current rating: 1A@30VDC 0.5A@125VDC
- Voltage: 12VDC
- Wear resistant legend
- Security screws (allen key type)
- Internal or External use
- Button is rated at IP68
- Operating temperature: -20C to 50C
- Standby: 12VDC 4.63mA (operating - 14.71mA)

IEPS/PTE

- Stainless steel piezo button
- Momentary operation
- LED status:
 - Red: Standby
 - Green: Operation
- No moving parts
- Can be surface or flush fitting
- Easy clean surface
- Ideal for general/sensitive areas
- Screw footprint for flush fitting onto standard back box
- Distance between fixing holes 60mm

EBCBWC02/DR



EXTR02



DIMENSIONS

IEPS/PTE


- 85H x 85W x 28D (mm)
- 240g (Boxed)
- 198g (Unboxed)

CONTENTS

IEPS/PTE

- Illuminated Piezo Switch
- Stainless Steel Plate (2mm)
- 2 Security Screws
- Allen Key
- Surface Box

ML600



Manufactured by a BSIA Member

DU-GB/PTE

