

LED MONITOR

LME215HD4

LED Monitor

PD654DS215AHDA-4KLED

Panel Type	21.5" LED Monitor
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	476.64 (H) x 268.11 (V) mm
Pixel Pitch	0.24825 (H) x 0.24825 (V) mm
Bezel Thickness	Left/Right/Top 25mm Bottom 36mm
Contrast Ratio	1000 : 1
Brightness	250 cd/m ²
Response Time	5 m.sec
Viewing Angle	178° / 178°
Display Colours	16.7m
Video Synchronisation	Yes
PC Compatibility	N/A
Aspect Ratio	16:9
VGA Auto Frequency Correction	N/A
Speakers	NO
Sound Demodulation	NO
Mute	N/A
Work Humidity	5% - 90%
Work Temperature	0 - 40 °C
Power On/Off	Yes



IN / OUT INTERFACE

Video Interface	2 x HD analogue BNC in (CVBS, AHD, CVI, TVI) 2 x HD analogue BNC out (CVBS, AHD, CVI, TVI) HDMI in
Audio	N/A
Power Interface	DC in x 1
Certification	FCC-DOC, CE, ROHS
VESA	100 x 100
Stand Type	Desk
Colour	Black
Button Position	Front, Bottom Right
Packing Dimensions	580 x 120 x 440mm
Nett Weight	24.59 Kkgs
Gross Weight	4.5 kg

POWER

Power Supply	220/240 AC
Voltage	12v DC
Power Consumption	21<25Watt

OSD CONTROLS

Contrast, Brightness, Saturation, Hue,
Contrast, Brightness, Saturation, Hue
Language, OSD position, OSD Time, Reset

OSD LANGUAGE

English, English, French, Italian, German, German, Spanish, Spanish, French, Italian,

Dutch, Polish, Russian, Danish

Russian, Polish, Danish

ACCESSORIES

Power cord, Adapter, Stand, User's guide,
HDMI cable

