

MPN: 0070-05852

PTZ 30x zoom 1080p, 120dB UWDR Mini Bracket, POE+, 24VAC, EIS, H.264, H265, MJPEG, OnVif

The Orion DX 5 is a full HD IP speed dome camera featuring Sony's IMX462 Starvis™ back-illuminated pixel technology CMOS image sensor producing a colour sensitivity of 0.18Lux offering a massive improvement in light sensitivity. The dome also includes an integrated motorised 30x optical zoom with autofocus. It The Orion DX 5 is a full HD IP speed dome camera featuring Sony's IMX462 Starvis™ back-illuminated pixel technology CMOS image sensor producing a colour sensitivity of 0.18Lux offering a massive improvement in light sensitivity. The dome also includes an integrated motorised 30x optical zoom with autofocus.

Orion DX 5 offers easy and reliable installation with High Power over Ethernet (PoE+ ultra) which simplifies installation since only one cable is needed to carry power as well as video and PTZ controls. The camera mount is designed with easy bayonet mounting enabling connection to the wide range of Ernitec mounting accessories, including ceiling, wall, pole or corner installations.



- 30fps @ 1080p
- High Dynamic Range 120dB
- EIS Ernitec Image Stabilization
- 30x P-Iris Zoom Lens
- H.264 & H.265
- De-Fog
- PoE + (IEEE 802.3at)
- 3 year Warranty

Specifications

Audio	Audio formats supported	G.711, G.726
	Audio input channels	1 kan.
	Audio output channels	1 kan.
Camera	Camera pan control	No
	Pan range	0 - 360 °
	Tilt angle range	-15 - 90 °
	White balance	ATW, Auto, Indoor, Outdoor, Fluorescent
Design	Form factor	PTZ Dome
	IK code	IK10
	International Protection (IP) code	IP66
	Mounting type	Ceiling/wall
	Product colour	White
	Protection features	Dust resistant, Water resistant
	Weatherproof	Yes
Features	NDAA Compliance	Yes
Image sensor	Number of sensors	1

Image sensor	Optical sensor size	1/2.8 "
	Progressive scan	Yes
	Sensor type	IMX462
Lens system	Auto focus	Yes
	Digital zoom	12 x
	Focal length range	4.3 - 129 mm
	Focus	Motorized/Manual
	Optical zoom	30 x
	Zoom capability	Yes
Management features	Web browser	Yes
	Web-based management	Yes
Network	3G	No
	4G	No
	Bluetooth	No
	Cabling technology	10/100/1000BaseT(X)
	Ethernet interface type	Gigabit Ethernet
	Ethernet LAN	Yes
	Networking standards	IEEE 802.3at
	Number of users	20 uživatel/ů
	Quality of Service (QoS) support	Yes
	Streaming method	Multicast
	Supported network protocols	ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, HTTP, HTTPS, FTP, NTP, DDNS
	Wi-Fi	No
	Works with Apple HomeKit	No
	Works with the Google Assistant	No
	Operational conditions	Operating relative humidity (H-H)
Operating temperature (T-T)		-40 - 50 °C
Other features	Noise detection	Yes
	Number of simultaneous users	20 uživatel/ů
Package dimensions	Depth (package,cm)	30 cm
	Gross Weight (Package, kg)	5.4 kg
	Height (package,cm)	40 cm
	Width (package,cm)	30 cm
Packaging content	Number of cameras	1
	Quick installation guide	Yes
	Quick start guide	Yes
Performance	Auto patrol mode	Yes

Performance	Built-in fan	Yes
	Built-in heater	Yes
	Connectivity technology	Wired
	Placement supported	Indoor & outdoor
	PTZ control	Yes
	PTZ modes	4 Pattern
	Thermal module	No
	Type	IP security camera
	Wide Dynamic Range (WDR)	Yes
Ports & interfaces	Ethernet LAN (RJ-45) ports	1
	Interface	RJ-45
Power	Power consumption (max)	55 Watt
	Power over Ethernet (PoE)	Yes
	Power source type	DC, PoE+
Product dimensions	Net Weight (Product, kg)	5.300000000000001 kg
	Product Depth	20 cm
	Product Height	35 cm
	Product Width	20 cm
Security	HTTPS encryption	Yes
	IP address filtering	Yes
	Video motion detection	Yes
Storage	Built-in HDD	No
	Built-in SSD	No
	Card reader integrated	Yes
	Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
	Maximum memory card size	128 GB
Technical details	Sensor	IMX462
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	3 Year(s)
Video	3D NR (Noise Reduction)	Yes
	Analog signal format system	NTSC, PAL
	Frame rate	30 fps
	Full HD	Yes
	Image stabilizer	Yes
	Maximum resolution	1945 x 1097 Pixels
	Noise reduction	Yes
	Noise reduction technology	3D noise reduction
	Privacy masking	Yes
Total megapixels	2 MP	

Video

Video compression formats	H.264, H.265, M-JPEG
Video streaming	Yes