

Datasheet

PROXIMIY READERS/ DG502-UP - 2-door controller

Product description

The DG502-UP is a high quality 2-door controller, which is simple to install, programme and maintain.

The DG502-UP is a flexible controller able to manage 2 doors with independent access levels, or read in and out on 1 door. It is suitable for standard locking requirements or more critical fire escape routes.

Simple programming via a master code allows the adding and deleting of users and the setting of the lock time. The option is CARD, CARD+PIN or PIN.

Digicode®



Key features

- 2-door controller
- Up to 500 users
- Connection to CDVI readers
- Audible and visual feedback

 **Green**
Door relay activated

 **Orange**
Stand-by

 **Red**
Alarm activated

 Certification

 DEEE

RoHS Certification

All the information contained within this document (pictures, drawing, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. - April 2020 - CDVI_DG502-UP_DS_01_EN_A4_C

Product information

Material: polycarbonate

Operating Voltage: 12vdc/ac

Card entry: up to 500

Codes: up to 500

Input: 2 exit buttons

Output: 2 form C relays

N/O and N/C 3A @ 125V

Relays: 2, timed/ latching relay outputs

Electrical Specifications

Power supply: 12Vac/dc

Power Consumption: 200mA

