

Datasheet

ML-300-SW - Reversible Electric Lock


Product Description

The ML Range of electric locks are high performance locks suitable for double action doors.

The ML-300-SW provides Euro cylinder operation in the ML series locking range, suitable for vertical mounting and double action door sets.

Manufactured from stainless steel and featuring 650kg holding force, this lock is field selectable between fail safe and fail secure installations.

With lock status monitoring and tested to 1,000,000 cycles, the ML-300-SW is a great solution for doors requiring solenoid type locking arrangement with Euro cylinder provision, featuring high quality and long-life operation.



Key Features

- Reversible fail safe or fail secure electric lock
- Up to 650kg holding force
- Suitable for double action doors
- Euro cylinder provision
- Suitable for vertical mounting
- Tested for 1,000,000 cycles
- Lock status monitoring

 Certification

 DEEE

RoHS Certification

 -10°C to 49°C

All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 26 October 2021. CDVI_ML-300-SW_DS_01_EN_A4_C

Product Specifications

- Material:** Stainless steel
Mounting: Vertical
Holding force: Up to 650kg
Cycles: Tested to 1,000,000
Actions: Single and double action doorsets
Dimensions:
- Strike: 275 x 44 x 25 mm
 - Faceplate: 150 x 40 (30 mm backset) x 1.5 mm
150 x 50 (30 mm backset) x 1.5 mm

Electrical Specifications

- Power input:** 12/24 Vac/dc
Consumption: 250mA @ 12Vdc
150mA @ 24Vdc
Lock status contact rating: 1.5A @ 250Vac

