



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT





**KVV8111**

## VISTO ViP KIT WITH POWER SUPPLY UNIT

### KIT PRODUCTS



#### **VS8111 VISTO WI-FI EXTERNAL UNIT. ViP SYSTEM**

Wi-Fi video entry external unit for use in Comelit ViP systems, complete with adapter allowing use of the power supply for the existing bell (12-20 VAC or 12-33 VDC) and allowing interfacing with the existing bell. Depending on the system configuration, you can receive video entry phone calls on ViP monitors or directly on smartphones and tablets via the Comelit app. With the Comelit app, you are always in touch with what is going on at your home, whether you are in town or even in another country.

#### GENERAL DATA

|                     |                       |
|---------------------|-----------------------|
| Type                | Monoblock             |
| Product height (mm) | 136                   |
| Product width (mm)  | 47                    |
| Product depth (mm)  | 32                    |
| Product colour      | Dark Graphite RAL9011 |
| Material            | Plastic               |
| Wall-mounted        | Yes                   |

#### COMPATIBLE SYSTEMS

|     |     |
|-----|-----|
| ViP | Yes |
|-----|-----|

#### AUDIO FEATURES

|                          |  |
|--------------------------|--|
| Technologies implemented | Full-Duplex, Echo canceling, Noise reduction |
|--------------------------|--|

#### CAMERA FEATURES

|                           |                |
|---------------------------|----------------|
| Camera                    | Colours        |
| Sensor type               | 1/4" CMOS      |
| Lens (mm)                 | 1.6            |
| Angle of view (H x V - °) | 170 (diagonal) |
| Sensitivity (lux)         | 2              |



**KVV8111**

**VISTO VIP KIT WITH POWER SUPPLY UNIT**

**CAMERA FEATURES**

|                            |            |
|----------------------------|------------|
| Resolution (H x V - pixel) | 1280 x 720 |
| Video compression          | H.264      |

**ELECTRICAL CHARACTERISTICS**

|                        |                       |
|------------------------|-----------------------|
| Type of power supply   | External power supply |
| Supply voltage         | 12÷33 VDC             |
| Maximum absorption (W) | 6                     |

**HARDWARE FEATURES**

|                             |                        |
|-----------------------------|------------------------|
| Call type                   | Push-buttons           |
| Type of buttons             | Mechanical             |
| Number of push-buttons (n°) | 1                      |
| Clamps                      | + - NO C               |
| Removable terminals         | Yes                    |
| Number of outputs (n°)      | 1                      |
| Type of outputs             | Relay (C-NO, 1A@30VDC) |

**NETWORK AND COMMUNICATION PROTOCOLS**

|                          |         |
|--------------------------|---------|
| Type of Wi-Fi connection | 2.4 GHz |
|--------------------------|---------|

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

|                                     |  |
|-------------------------------------|--|
| IP protection degree                | IP54   |
| Operating temperature (°C)          | -25 ÷ 55   |
| Operating humidity (RH max - %) (%) | 0 ÷ 75   |
| Environmental class                 | III  |
| Compliance and Certifications       | RoHS II - 2011/65/UE (EN 50581:2012), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1) |



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT

### MAIN FUNCTIONS

|                                     |     |
|-------------------------------------|-----|
| Visual indications of system status | Yes |
|-------------------------------------|-----|



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT



**1595 120-230VAC / 33VDC POWER SUPPLY UNIT**

Power supply unit with input of 120÷230VAC, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

### MAIN FEATURES

|                            |             |
|----------------------------|-------------|
| Supply voltage             | 120÷230 VAC |
| Output supply voltage      | 33VDC       |
| Max. current delivered (A) | 0.5         |
| Maximum inrush current (A) | 1.2         |
| Applicable to DIN rail     | Yes         |
| Number of DIN modules (n°) | 4           |

### GENERAL DATA

|                               |          |
|-------------------------------|----------|
| Height (mm)                   | 62       |
| Width (mm)                    | 71.7     |
| Depth (mm)                    | 90       |
| Type of finish                | Plastic  |
| Colour                        | White    |
| Operating temperature (°C)    | -20 ÷ 40 |
| Operating humidity (% RH max) | <90      |

### COMPATIBILITY

|                                 |     |
|---------------------------------|-----|
| Simplebus 2 audio/video system  | Yes |
| Building Kit audio/video system | Yes |
| Simplebus 2 audio system        | Yes |
| Simplebus 1 audio system        | Yes |
| Vip system                      | Yes |
| Kit audio/video system          | Yes |



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT

### ELECTRICAL SPECIFICATIONS

|                             |    |
|-----------------------------|----|
| Maximum power delivered (W) | 60 |
|-----------------------------|----|