



**UT9310M**

**MAGNETIC INDUCTION MODULE, ULTRA**



**AWARDS**

DESIGN  
MILANO



**UT9310M**

**MAGNETIC INDUCTION MODULE, ULTRA**

**GENERAL DATA**

Type	Modular
Product height (mm)	90
Product width (mm)	100
Product depth (mm)	35
Product colour	Aluminum
Material	Polycarbonate, Aluminium alloy
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio/video Simplebus 1	Yes
Audio Simplebus 1	Yes
ViP	Yes

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Absorption in stand-by (mA)	0.73
Maximum absorption (W)	8

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max - %) (%)	25 ÷ 95
Environmental class	III



**UT9310M**

**MAGNETIC INDUCTION MODULE, ULTRA**

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
-------------------------------	--

**FEATURES**

Operating humidity (% RH max)	95
-------------------------------	----