

**4681/4****A/V UNIT FOR MAX. 4 USERS. S2**

Colour audio-video unit for 2-wire systems with terminal block complete with directable colour camera with front adjustment, LED camera lighting, max 4 users.. Complete with terminal block and audio control with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Complete with microprocessor and 8-position dip switch for programming calls to users. Programmable audiovisual functions for users with disabilities. On-board electronic lock-release function (3A) plus C, NC, NO contacts for 10A relay. Timed lock-release input and door open indication. Compatible with power supply unit art. 1210. Dimensions: 102x55x38 mm.



4681/4

A/V UNIT FOR MAX. 4 USERS. S2

GENERAL DATA

Type	Audio and video unit
Height (mm)	102
Width (mm)	55
Depth (mm)	43
Product color	White
Product weight (g)	200
Type of finishing materials	ABS

COMPATIBLE SYSTEMS

Simplebus 2 audio/video kit with power supply art. 1209	Yes
---	-----

AUDIO FEATURES

Microphone	9.7 (∅), omnidirectional
Loudspeaker	50mm (∅), 8 Ohm, 0.2W
Technologies implemented	Echo canceling

CAMERA FEATURES

Camera	Colours
Sensor type	1/3" CMOS
Sensitivity (lux)	0.35 (F2.0 / 50IRE)
Camera orientation	Vertical

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus, External power supply
Supply voltage	33VDC
Maximum absorption (W)	13

HARDWARE FEATURES

Clamps	L L V+V- RTE DO PR GND SE COM NC NO
--------	-------------------------------------



4681/4

A/V UNIT FOR MAX. 4 USERS. S2

HARDWARE FEATURES

Removable terminals	Yes
Number of inputs (n°)	2
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC), SE: unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum impedance 18 Ohm)

SETTINGS

Loudspeaker volume	Yes
--------------------	-----

PROGRAMMING MODE

Manual programming (via Dip Switch)	Yes
-------------------------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes
Visual indications of system status	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes