

**6701W****SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET**

SIMPLEBUS2

Wall-mounted colour monitor with 4.3" 16:9 screen and handset. Allows brightness and contrast control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 4 soft touch buttons for door-opening, self activation, switchboard call, silent mode and with door status indicator LEDs. Manages floor door calls as standard. Option of adding 4 additional buttons with accessory art. 6733W. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 175x160x22mm.

**AWARDS**DESIGN  
MILANO



**6701W**

**SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET**

**GENERAL DATA**

Height (mm)	160
Width (mm)	175
Depth (mm)	22
Product color	White RAL9003
Type of finishing materials	ABS
Product weight (g)	600
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

**DISPLAY**

Display size (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272

**AUDIO FEATURES**

Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (ø) x 5.1 (H)mm, 100 ohm, 0.25W

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Maximum absorption (W)	5.4



**6701W**

**SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET**

**HARDWARE FEATURES**

Type of buttons	Capacitive
Service buttons	Lock-release, Silent (Privacy), Door open
No. of programmable buttons for additional functions	2 (6 with accessory art. 6733W)
Clamps	L L CFP1 CFP2
Removable terminals	Yes

**SETTINGS**

Ringtone volume	Yes
Screen brightness control	Yes
Screen colour	Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**GENERAL FEATURES**

Door opening on call (Doctor)	Yes
Door opener	Yes
Self Activation	Yes
CPS call	Yes
Intercom calls	Yes
Actuator control	Yes
Multiple address	Yes
Outside door call input	Yes
Sending alarm calls	Yes



**6701W**

**SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET**

**GENERAL FEATURES**

Silent mode (Privacy)	Yes
Door open signaling	Yes
Customisable ringtone	Yes

**6701W****SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET****ACCESSORIES****6712A Desk base for Mini S2 monitor with handset**

Desk base installation accessory for Mini monitor with handset in Simplebus 2 system.

**6711WS MINI HANDSET SMALL ADAPTER PLAQUE**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. White. Dimensions: 230x220x3mm.

**6719W Access. cables external passage for MINI HS. S2**

Wall support bracket for Mini monitor with handset allowing thru-routing of external cables.

**6711W ADAPTER PLAQUE FOR MINI MONITOR W/ HANDSET. WHITE.**

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. Complete with backplate art. 6710. White. Dimensions: 300x270x3 mm.