



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



The kit includes: two Mini series door-entry phones art. 2701W, one transformer art. 1200, one Extra series external unit with 2 call buttons art. ET5002. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the relevant accessories supplied with the kit.

AWARDS





KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

PRODUCTS IN THE KIT



ET5002 EXTRA 4+N. SERIES ENTRANCE PANEL KIT. 2 BUTTONS

Extra series external unit with 2 call buttons. Stainless steel cover and white nameplate backlighting. Complete with flush-mounted box and wall bracket. Dimensions 95 x 135 x 6.5 mm (flush) - 25 mm (surface). 5-Wire cabling.

| GENERAL DATA | |
|---------------------------------------|------------------|
| Flush-mounted | Yes |
| Wall-mounted | Yes |
| HARDWARE FEATURES | |
| Clamps | ~* ~ 2 3 4 S1 S2 |
| ENVIRONMENTAL AND COMPLIANCE FEATURES | |
| Operating temperature (°C) | -25 ÷ 55 |



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



2701W 1-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Dimensions: 105x191x28 mm

GENERAL DATA

| | |
|--------------------|-------|
| Height (mm) | 190 |
| Width (mm) | 103 |
| Depth (mm) | 30 |
| Product color | White |
| Product weight (g) | 260 |
| Wall-mounted | Yes |
| Desk base-mounted | Yes |

COMPATIBLE SYSTEMS

| | |
|--------------------|-----|
| Traditional system | Yes |
|--------------------|-----|

AUDIO FEATURES

| | |
|------------|--------------------------|
| Microphone | 4mm (Ø), Omnidirectional |
|------------|--------------------------|

ELECTRICAL CHARACTERISTICS

| | |
|----------------|----------|
| Supply voltage | 15÷16VDC |
|----------------|----------|

HARDWARE FEATURES

| | |
|--------------------|------------|
| Clamps | S 2 3 4 P1 |
| Total buttons (n°) | 1 |

ENVIRONMENTAL AND COMPLIANCE FEATURES

| | |
|----------------------------|---------|
| IP protection rating | IP30 |
| Operating temperature (°C) | -5 ÷ 40 |

GENERAL FEATURES



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.

| | |
|--------------------------------------|------|
| Absorption during call (mA) | 0.42 |
| Absorption during communication (mA) | 0.35 |
| Key button function | Yes |
| Loudspeaker volume control | Yes |
| Microphone volume control | Yes |
| Ringtone volume control | Yes |
| Audio system | Yes |
| Electronic bell | Yes |



KAE5062

5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.



1200 TRANSFORMER 10VA 0-230V/0-12V

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES

| | |
|----------------------------|-----|
| Supply voltage | 230 |
| Applicable to DIN rail | Yes |
| Number of DIN modules (n°) | 3 |
| Max. current delivered (A) | 0.9 |

GENERAL DATA

| | |
|-----------------------------|---------|
| Height (mm) | 95 |
| Width (mm) | 53 |
| Depth (mm) | 65 |
| Type of finishing materials | Plastic |
| Operating temperature (°C) | -5 ÷ 40 |

COMPATIBILITY

| | |
|---------------------------------|-----|
| Simplebus 2 audio/video system | Yes |
| Building Kit audio/video system | Yes |
| Simplebus 2 audio system | Yes |
| Simplebus 1 audio system | Yes |
| Vip system | Yes |
| Kit audio/video system | Yes |
| Traditional system | Yes |
| Simplified system | Yes |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------------------|----|
| Maximum power delivered (W) | 15 |
|-----------------------------|----|

**KAE5062****5-WIRE TWO-FAMILY AUDIO KIT. EXTRA-MINI.****ACCESSORIES****ET9150 FLUSH-MOUNTED BOX FOR EXTRA ENTRANCE PANEL KIT**

Flush-mounted box for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 134.5 x 93.5 x 25 mm

**ET9160 WALL BRACKET FOR EXTRA ENTRANCE PANEL KIT**

Wall housing for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 94 x 134 x 19 mm

**1229 EXTENSION SOUNDER**

Additional bell for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surfacemounted or on civil series 503 box. Dimensions: 110X75X29 mm.