



GAA-001

Genie Audio Amplifier

Genie covert microphone with built in preamp. Can be used in conjunction with various Genie DVRs and cameras.



GAA-001

Key Features

- Covert Style
- Up to 80 sq.m monitoring range
- -30dB Sensitivity
- Overload Protection
- Power In/Power Out Connection

Technical Specification

Model Number	GAA-001
Monitoring Range	10 ~ 80 (sq.m)
Transmitting distance (Shielded Cable)	Up to 2km
Frequency Response	20Hz ~ 20kHz
Sensitivity	-30dB
SNR	70dB(1m/40dB) 40dB(10m/40dB)1KHz at 1 Pa
Polar Pattern	Omni-Directional
Dynamic Range	104dB (1 KHz at Max dB SPL)
Maximum Level Input	120dB SPL (1 KHz, THD 1%)
Impedance	600ohm (imbalance)
Signal Output Extent	2.5Vpp/-25db
Microphone	Electret condenser
Special Circuit	DSP de-noise, AGC circuit
Protect Circuit	Over-load protection
Audio Preamp	Built-in
Output Connector	Power+, Audio and Public GND
Voltage	DC12V (9 ~ 12V)
Current	20 mA
Temperature	-25°C ~ 70°C
Material	PVC
Dimensions (mm)	3 x 0.5

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Accessories

- GAIPLEAD - IP Audio Lead