


NDAA Compliant 4/8/16 Channel NVRs

VIP-NVR0408MP, VIP-NVR0808MP & VIP-NVR1608MP



KEY FEATURES

NDAA compliant - NOVATEK chipset

Available in 4, 8 & 16 channels

8MP IP camera support

4K output

Analytics (with supported cameras)

Vista Vizion mobile and PC applications (FOC)

Corridor mode

Support H.265/H.264 video formats

Plug & play with 4/8/16 independent PoE network ports

ONVIF Profile S, G and T

Vista's VIP series of NVRs are fully NDAA compliant, allowing you peace of mind in offering one, consistent range that satisfies requirements across both private business and public sector projects.

The VIP 4/8/16 channel network video recorders support up to 8MP cameras along with 4K monitors.

With the VIP Series you will benefit from SMART video analytics including Intrusion, Cross Line, Enter & Leave Area, Defocus, Scene Change, Object Left/Removed, Auto Tracking, People Flow Counting.

Integral to the recorders is Vista's range of client and mobile software - Vizion. Vizion Remote allows you to control PTZ cameras, view live and recorded footage, manage devices and event push notifications, all remotely.

Vizion Desktop is a PC Based viewing client for Windows & Mac OS systems, easy to deploy video management software, with features such as live view, playback, device management, recording schedule, alarm configuration, video wall, people counting, and e-map.

The NVRs also offer both audio and alarm input and output. If you need additional features such as evidence review, Raid capability or 32 channels input consider Vista's VIP 12MP NVRs.

To learn more about Vista's NDAA compliant video surveillance products please visit www.norbain.com/brands/vista



TEL
+44 (0) 118 912 5000



* To scan the QR code, make sure your phone/device has a suitable reader. Most modern Android and iOS smartphone cameras will automatically scan the code and provide the product's URL link, which will open from the device's web browser.

TECHNICAL SPECIFICATION

Model	VIP-NVR0408MP	VIP-NVR0808MP	VIP-NVR1608MP	
VIDEO				
Video Input	4 × IP	8 × IP	16 × IP	
Video Input Resolution	8MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Compression	H.265, H.264			
Display Output	1 VGA, 1 × 4K HDMI			
Max Display Resolution	VGA: 1920 × 1080p/50Hz; HDMI: 3840 × 2160 (4K) max			
Display Mode	1/4	1/4/6/8/9	1/4/6/8/9/16	
RECORDING				
Dual Stream Record	Yes – high and low res			
Recording Mode	Continuous/Schedule/Motion/Alarm/Event			
Recording Bandwidth	80Mbps		160 Mbps	
PLAYBACK				
Decoding Capability	2 × 4k@30; 3 × 5MP@30; 4 × 4MP@30	2 × 4K@30; 4 × 4MP@30; 5 × 3MP@30; 8 × 1080P @30	2 × 4K@30; 4 × 4MP@30; 5 × 3MP@30; 8 × 1080P@30; 16 × 720P@30	
Simultaneous Playback Channels	1 to 4	1 to 8	1 to 16	
STORAGE				
Internal HDD	1 × SATA HDD (8TB max)	2 × SATA HDD (10TB max)		
RAID	n/a			
External Storage eSATA	n/a			
Backup	USB memory stick or USB DVD Burner*			
Backup File Format	MP4 default to USB or .TS to Disc			
AUDIO				
Compression	G.711A/U			
Sample bit rate	8Khz 16-bit 64Kbps			
FUNCTION				
SMART Video Analytics (Supported Cameras)	Intrusion, Cross Line, Enter & Leave Area, Defocus, Scene Change, Object Left/Removed, Auto Tracking, People Flow Counting			
User Interface	Mouse, virtual keyboard, WEB browser, PC-Based VMS-Vizion Software			
NETWORK				
Ethernet	WAN	1 × RJ45 10/100	1 × RJ45 10/100/1000	
	PoE	4 × RJ45 10/100	8 × RJ45 10/100	16 × RJ45 10/100
	PoE Standard	IEEE 802.3af/at		
	PoE power port Switch Total	30W Max 54W	30W Max 130W	30W Max 240W
Max Bandwidth out	64Mbps			
ONVIF	Profile S, G and T			
Remote Monitoring	Vizion Remote Android/IOS mobile app and Vizion Desktop Windows/Mac PC Application			
Browser Support	IE(10/11), Firefox (ver 52.0), Chrome (ver 45), Edge (ver 79) minimum			
Protocols	P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP			
EXTERNAL IN/OUT				
Audio In Out	1 × RCA 1 × RCA, 1 × HDMI			
Alarm In Out	n/a n/a	4 1		
Serial Port	n/a			
USB	1 × USB2.0, 1 × USB3.0			
GENERAL				
Operating Temperature	-10°C-55°C (14°F-131°F), Humidity ≤ 90% RH (non-condensing)			
Power Supply	48VDC	100-240VAC		
Power Consumption	<10W (No HDD/PoE) <75W (full)	<10W (No HDD/PoE) <170W (full)	<15W (No HDD/PoE) <280W (full)	
NET Dimension (WxDxH) Weight	260mm × 240mm × 47mm (10.2" × 9.4" × 1.9") ≤1kg (2.20 lb)	380mm × 315mm × 53mm (15.0" × 12.4" × 2.1") ≤2.6Kg (5.73lb)		
COMPLIANCE				
NDAA Compliant	Yes, Novatek chipset			

* Supported DVD Burner LG GP65NB60

MODELS IN THIS RANGE

0910620 VIP-NVR0408MP

4CH 8MP H.265 HD PoE NVR

0910630 VIP-NVR0808MP

8CH 8MP H.265 HD PoE NVR

0910640 VIP-NVR1608MP

16CH 8MP H.265 HD PoE NVR

OTHER PRODUCTS

0913720 VistaPC-i5-G12-3Mon-KBM ClientPC

Windows Client i5 PC with OTB storage, 3-monitor support

0913730 VistaPC-i5-G12-3Mon-KBM-2TB Srv/Client

Windows Client i5 PC with 2TB storage, 3-monitor support

0338110 VFS118WHDA 18.5"

Monitor TVI/AHD/CVBS/HDMI & VGA

0773530 VFS121WHDA 21"

Monitor TVI/AHD/CVBS/HDMI & VGA

0908420 VSW4

4 port PoE switch dual uplink

0908430 VSW8

8 port PoE switch dual uplink

0908440 VSW16

16 port PoE switch dual uplink

0908450 VSW24

24 port PoE switch dual uplink

0872170 DIAMOND4K

All in one CCTV\IP\Cable Test Monitor

