



Installation Devices / Installation Devices: Interface, Relay,Activ,Acc/Call

Product Code

F03267

## DUOX PLUS RELAY

Reference EAN  
3267 8424299032672

### Description.

#### Description

The DUOX PLUS Relay allows for dry contacts in DUOX PLUS system, with various operating and activation modes to be configured:

- Relay activation using commands generated from the residential terminals, entry panels or guard units.
- External activation using buttons, additional external switches, etc.

The DUOX PLUS relay can be installed in any part of the DUOX PLUS bus. You can install one or several relays: by apartment, block or installation.

**System: DUOX PLUS (2 wires digital).**

#### Technical Details

- Power supply: 18 - 24 Vdc (non-polarised, via the BUS INPUT or BUS OUTPUT).
- Consumption:
  - \* In standby: 1,24 W.
  - \*Maximum: 4,4 W.
- Operating temperature: [0, 40°C].
- IP Address: 20.
- (+12V): Auxiliary voltage output 12Vdc (300 mA max).
- Dry contact relay:
  - C: Common.
  - NC: Normally Closed.
  - NO: Normally Open.
  - \* Maximum current 3A.
  - \* Maximum voltage 250 VAC or 30 VDC.

## Details.

---

Weight (kg)

0.365543

Dimensions (cm)

7,5x23x17,8

Video Door Entry system

Technologie

DUOX

### Manuals

[97821b\\_Rele\\_DUOX\\_V12\\_19.pdf](#)

[97822Ac Man Avanzado Rele DUOX PLUS ref 3267 V11\\_20.pdf](#)

[97822Ec Man Avanzado Rele DUOX PLUS ref 3267 V11\\_20.pdf](#)

[97822Fc Man Avanzado Rele DUOX PLUS ref 3267 V11\\_20.pdf](#)

[97822Ic Man Avanzado Rele DUOX PLUS ref 3267 V11\\_20.pdf](#)

[97822Pc Man Avanzado Rele DUOX PLUS ref 3267 V11\\_20.pdf](#)

### Declaration of conformity

[DOCF03267EN.pdf](#)