



Product Code

F05481

MARINE VIDEO PANEL VDS DIG. ST4 WITH PROXIMITY

Reference

EAN

5481

8424299054810

Description.

Description

Dialling keypad.

Fermax Marine Line in stainless steel.

Marine is the anti-vandal panel line manufactured in 2.5 mm thick stainless steel.. Straight lines that highlight the quality of the steel. State of the art technology and resistance to even the most corrosive, humid and dangerous atmospheres.

Reader that enables door opening when a proximity card, similar to a credit card, approaches. Only authorized cards will activate the device. No physical contact is necessary.

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc. Incorporates COLOUR camera with built-in lighting and pan&tilt regulation system to adjust the camera lens.

Backlit LCD 2 line display, 16 characters each.

Colour aluminium

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

Technical Details

Audio capacity home-outdoor panel: 2W

Audio power direction apartment-outdoor panel (speakers): 2 x 2W

IP54 IK09

Details.

Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie	Access Control Technology
2.837332	49,6x16,4x8,2	VDS	PROXIMIDAD

Manuals

- 970112_Normativa_Modulo_radiofrecuencia_V10_17.pdf
- 97486g_Man_Prog_Placas_Direct-Dig_VDS-BUS2-DUOX_V04_14.pdf
- 97486Pg_Man_Prog_Placas_Direct-Dig_VDS-BUS2-DUOX_V09_14.pdf
- 97516b_M_Inst_Placas_NCity-NMarine_Direct-Digital_VDS_V07_14.pdf
- 97597Ac_Lector_Proximidad_Autonomo_NCity_V09_16.pdf
- 97597Ec_Lector_Proximidad_Autonomo_NCity_V09_16.pdf

97597Fc_Lector_Proximidad_Autonomo_NCity_V09_16.pdf
97597Ic_Lector_Proximidad_Autonomo_NCity_V09_16.pdf
97597Pc_Lector_Proximidad_Autonomo_NCity_V09_16.pdf
97598c_Lector_Proximidad_Centralizado_NCity_V09_16.pdf
97737_Limpieza_Placas_Marine_V04_20.pdf

Declaration of conformity

DOCF05481EN.pdf